

**ilShin<sup>®</sup> America**

*Delivering Quality Through Service*



Products



- Upright Freezers
- Chest Freezers
- Freeze Dryers
- Ice Flake Machines
- Blood Bank Refrigerators
- Chromatography Chamber
- Optional Accesories

**Blood Bank Refrigerators**



**Blood Bank Refrigerators**

All temperature configurations offer forced air circulation by internal fans to ensure high temperature uniformity and fast temperature recovery. Our line is available in single door (557 liter), Double door (1251 liter).

The philosophy behind our Refrigerators line is to offer the safest environment for your products by using our temperature control system in combination with the circulating forced air.

- Only ilShin Refrigerator that uses standard Stainless Steel interior and exterior on all refrigerator products;
- Microprocessor control with digital display / controller
- Adjustable temperature set points;
- High temperature Alarm;
- Low temperature alarm;



- Dry contact for remote alarm;
- Door open alarm;



- Light on/off(in case of glass door);
- Auto switch off fan when door opens;
- Automatic defrost cycle and melt water evaporation in heated tray;
- Heavy-duty casters with unique built in adjustable stand;
- Chamber with rounded corners for easy cleaning;
- 60 mm of CFC-free polyurethane foam insulation;
- Always pass through standard doors because of Slimline® design: only 80 cm wide and 198 cm high.

**For more information download following brochure:**

**Standard specifications slimline blood bank refrigerators:**

Model no:	BB0123	BB0150
Capacity:	557 Liters	1251 Liters
Temperature Range:	Temperature is factory set at 4°C with a range of 0°C to 13°C	
Exterior Dimensions	740(W) x 830(D) x 1910(H) mm	1500(W) x 803(D) x 1910(H) mm
Interior Dimensions	610(W) x 630(D) x 1450(H) mm	1370(W) x 630(D) x 1450(H) mm
Material:	All stainless steel internal	
Refrigeration:	1/3 Hp. Hermetically sealed compressor	1/2 Hp. Hermetically sealed compressor
Drawers:	6 Adjustable solid stainless steel drawers	12 Adjustable solid stainless steel drawers/p>
Door:	1 Double-paned temperature glass doors	2 Double-paned temperature glass doors
Interior Light	15 Watt fluoresent interior lights	40 Watt fluoresent interior lights
Certification:	KGMP, ISO14001, ISO9001 certified	
Electrical:	AC 200 / 230V, 50/60 Hz	
Noise Level:	45 dB	
Weight:	119 Kg	173 Kg